

## Steam generators



### GV Katla











- Saturated steam at 9 bar at a temperature of 175°C
- Steam gun with low tension control
- S. S. body AISI 304
- Boiler 3,3 kW S. S. AISI 304. Thickness 25/10
- Low level water lamp indicator
- Device for using chemicals and detergents mixed with steam
- Heating and activation time required: 7 min.
- Steam regulation
- Discharge valve
- Pressure gauge
- The boiler can be refilled from the tank provided (continuous duty)
- Wheels suitable for food and processing areas
- Storage basket.

#### GV Katla

Code	8.453.0001
Absorbed power	3,3 Kw/230 V-Ph1
Max pressure	9 bar
Steam production	4,62 Kg/h
Max temperature	175° C
Water tank capacity	5 l.
Detergent tank capacity	5 l.

### GV Katla

#### Standard equipment:

• 5.409.0256	
• 3.753.0111	
• 3.754.0228	
• 3.754.0229	
• 3.754.0235	
• 3.754.0250	
• 3.754.0230	
• 6.405.0240	
• 6.402.0096	
• 3.754.0234	
• 6.402.0095	
• 3.099.0126	

**Optional** • 5.409.0254 Steam gun with hose (10 m)



Watch the video on youtube:  
[www.youtube.com/fasavideo](http://www.youtube.com/fasavideo)